

Brand		Maxivent by Econox	
Model		HP HRU 300	
Rated airflow		CMH	300
Exhaust airflow (ventilation mode)		CMH	300
Exhaust airflow (heating/cooling mode)		CMH	300
External static pressure		Pa	100
Ventilation mode	Temperature efficiency (heating)	%	79
	Temperature efficiency (cooling)	%	73
	Enthalpy efficiency (heating)	%	76
	Enthalpy efficiency (cooling)	%	71
	Input power	W	172
	Input current	A	1.4
Cooling RA:27/190C OA:35/240C	Nominal cooling capacity	W	2450
	Max cooling capacity (350CMH)	W	2670
	Input power (cooling)	W	1113
	Operation current (cooling)	A	5.41
Heating RA:20/120C OA:7/-0C	Nominal heating capacity	W	3130
	Max heating capacity (350CMH)	W	3470
	Input power (heating)	W	920
	Operation current (heating)	A	4.52
Noise		dB(A)	37 / 42
Power			220V 1Ph 50/60Hz
Dimension (W*L*H)		mm	600*760*1342
Weight		kg	157
Air inlet/outlet diameter		mm	195
Air inlet/outlet height		mm	40
Unit base height		mm	40
Drainage pipe		mm	32
Refrigerant			R32
Global warming potential			675
CO2 equivalent			0.203 tonnes
Refrigerant charge		g	370