


# DATA SHEET

## CO<sub>2</sub> control SEN CO<sub>2</sub>

**ruck**.eu  
VENTILATOREN



Type	ID	A mm	B mm	C mm	Weight kg
<b>SEN CO<sub>2</sub></b>	126586	100	85	26	0,09
<b>SEN CO<sub>2</sub>-OPTION *</b>	127338	100	85	26	0,09

\* The sensor is mounted in the device and completely wired.

- Protection class IP 30
- Long-term stable double-beam infrared cell
- For variable air volume control in meeting rooms

### Description:

The SEN CO<sub>2</sub> sensor combines CO<sub>2</sub> und temperature measurement in one housing. The CO<sub>2</sub> measurement is based on the infrared principle. A patented auto-calibration procedure compensates the aging of the infrared sensor and realizes the Long term stability.

### Technical data:

#### Measuring values

CO <sub>2</sub>	Measurement principle	Non-Dispersive Infrared Technology (NDIR)
	Sensor	Dual Source Infrared System
	Working range	0...2000 ppm
	Accuracy at 25 °C	
	and 1013 mbar	0...2000 ppm: < ± (50 ppm +2 % v.Mw.)
	Response time t <sub>63</sub>	< 195 s
	Temperature dependence	typ. 2 ppm CO <sub>2</sub> / °C
	Long term stability	typ. 20 ppm / a
	Sample rate	ca. 15 s
Temperature		
	Accuracy at 20 °C	± 0,3 °C

#### Output

Analogue output	0...2000 ppm	0 - 10 V
	0...50 °C	0 - 10 V

-1 mA < I<sub>L</sub> > 1 mA

#### General

Supply voltage	24 V AC ± 20 %	15 - 35 V DC
Current consumption	typ. 10 mA	+ Output current max. 0.5 A for 0.3 s
Warm up time	< 5 min	
Housing / Production class	PC / IP 30	
Electrical connection		Screw terminals max 1.5 mm <sup>2</sup>
Electromagnetic compatibility	EN61326-1	
	EN61326-2-3	

Working temperature range 0...90 % RH (non condensing) / -20...60 °C

Storage temperature range 0...90 % RH (non condensing) / -20...60 °C

### Connection Diagram:

